



Single line pull	4000lb
Motor	12V DC, 1.6HP permanent magnet
Gear train	SEALED 3 Stage Planetary metal gearing
Gear Ratio	136 : 1
Clutch	Cam activated
Braking Action	Mechanical & Dynamic
Drum size	Diameter 2.0" / Length 2.9"
Cable	55 ft of 1/4" Amsteel Blue cable
Battery	12 Amp/hour minimum
Mount Pattern	3" x 6.6"



Layer of Cable	Rated Line Pull Per Lbs
1	4000
2	3440
3	2958
4	2544



4,000 lbs Line Speed & Amp Draw (1st Layer)										
Pull	Lbs	No Load	500	1000	1500	2000	2500	3000	3500	4000
Line Speed	ft/min	26	20	16	14	11	8	7	6	4
Current	amps	31	70	106	141	175	224	245	268	308



Features	WARN XT 4000	VIPER ELITE EX4000SE
Dead-Pull Capacity	4000lb	4000lb
All Metal Drivetrain	Standard	Standard
Fully Sealed Drivetrain	Standard	Standard
Fully Sealed Winch Motor	Standard	Standard
Mechanical Braking System	Standard	Standard
Winch Control System	Handlebar & Wireless	Handlebar & Wireless
Weatherproof Winch Cover	Optional (\$27)	Standard
4T Snatch Block	Optional (\$30)	Standard
Flush Mounted Dash Switch	Not included	Standard
Winch Rope	7/32" x 50' generic synthetic	1/4" x 55' patented AMSTEEL-BLUE
Winch Rope Breaking Strength	5,200lbs	8,700lbs
Winch Rope Warranty	None	One year
Fairlead Style	Roller	Hawse for synthetic rope
Mechanical Warranty	Limited Lifetime	Two Years
Electrical Warranty	N/A	Two Years
Winch Specifications		
Winch Dimensions	14.4" L x 4.5" D x 4.7" H	14.4" L x 4.5" D x 4.7" H
Bolt Pattern	3.0" x 6.6"	3.0" x 6.6"
Line Speed (1000lb pull)	18.6 feet per minute	16 feet per minute
Line Speed (4000lb pull)	44.6 feet per minute	4 feet per minute
Motor Current (1000lb pull)	88	106
Motor Current (4000lb pull)	314	308
Gear Ratio	154:1	136:1 (faster speed)
Winch Weight	13.4lbs	15lbs
MSRP	\$625.99 - \$859.99	\$409.99 (w/o custom mount)